

CA 1001 Industrial thermocouple

Protection tube

Construction	Closed-end tube, diameter 9 mm.
Material	SS 316 - (Wst 1.4401)
Insertion length "L"	Customer to specify
Process connection	1 / 2" BSP

Connection head

Model	"B", according DIN 43729
Material	Cast aluminium
Cable entry	M20 x 1.5 cable gland

Measuring insert

Type	MI 1025
Construction	Springloaded and replaceable
Diameter	6 mm
Length "E"	E = L + 45 mm
Material	SS 316 - (Wst 1.4401)

Thermocouple

Calibration	K, T, J, E, N, U or L
For duplex	KK, TT, JJ, EE, NN, UU or LL
Accuracy	According IEC 584-1

Options


Transmitter 4-20mA	Head mounted transmitter, standard or ATEX Explosion. Choose from our standard range, see "Transmitter" section, specify make, model and range
Swing-Cover head	DAN. Transmitter direct mounted on measuring insert
High Swing-Cover head	DAN-H. Transmitter in cover. Insert with ceramic block

Thermokoppel kleurcodes

Thermocouple Extension Type	ANSI	IEC
JX + Iron - Constantan ®		
KX + Chromel ® - Alumel ®		
TX + Copper - Constantan ®		
EX + Chromel ® - Constantan ®		
NX + Nicrosil ® - Nisil ®		
SX + Copper RX - Alloy 11		
BX + Copper-S - Copper-E		

Toleranties volgens IEC 584-2

Type	Class	Temperature range	Fixed value °C	Tolerance to temp. t (°C)
T	1	- 40°C to + 350°C	± 0,5	± 0,004 · t
	2	- 40°C to + 350°C	± 1	± 0,0075 · t
	3	- 200°C to + 40°C	± 1	± 0,015 · t
E	1	- 40°C to + 800°C	± 1,5	± 0,004 · t
	2	- 40°C to + 900°C	± 2,5	± 0,0075 · t
	3	- 200°C to + 40°C	± 2,5	± 0,015 · t
J	1	- 40°C to + 750°C	± 1,5	± 0,004 · t
	2	- 40°C to + 750°C	± 2,5	± 0,0075 · t
	3	-	-	-
K and N	1	- 40°C to + 1000°C	± 1,5	± 0,004 · t
	2	- 40°C to + 1200°C	± 2,5	± 0,0075 · t
	3	- 200°C to + 40°C	± 2,5	± 0,015 · t
R and S	1	0°C to + 1600°C	± 1,0	± [1+0,003 · (t-1100)]°C
	2	0°C to + 1600°C	± 1,5	± 0,0025 · t
	3	-	-	-
B	1	-	-	-
	2	+ 600°C to + 1700°C	± 1,5	± 0,0025 · t
	3	+ 600°C to + 1700°C	± 4	± 0,005 · t



Ordering code

Model	CA 1001		
Calibration			
Insertion length "L" in mm			

H1-1 Rev.0 7/07



thermo-electra
temperature sensor solutions

Thermo Electra B.V.
Weteringweg 10
2641KM Pijnacker
The Netherlands

Phone +31 (0)15 - 3621200
Fax +31 (0)15 - 3694082
Email sales@thermo-electra.com
http://www.thermo-electra.com

